

TVP-3000 Multipurpose Network Barcode Printer

The preferred choice for thermal printers

- **High processing speed**
Advanced Motorola PowerPC processor provides high performance in high label production
- **Ruggedness**
Heavy gauge steel housing
- **Windows Compatible**
High quality labels can be produced with DIGI command language (DCL) or directly from any windows application software
- **Variable standard interface**
RS232, LAN, USB and parallel interface are equipped as standard
- **Web maintenance browser**
Time to set printer parameter with small LCD display is over. Internal Web Chip provides easy maintenance. Plug-in LAN cable and access it without any software installation. The printing parameter can be set and error browser view guides you through the trouble shooting process on the PC screen



Thank you to our loyal customers for their continued support



TVP-3000 Multipurpose Network Barcode Printer

INDUSTRIAL PRODUCTS

Specifications

printing method	direct thermal & thermal transfer
printing resolution	203 dpi (8 dots/mm)
MAX printing speed	8 ips (200mm/s)
MAX printing length	16" (400mm)
MAX printing width	4.25" (108mm)
fonts	5 alpha-numeric fonts. All fonts are expandable up to 24x24 4 directions 0° - 270° rotation soft fonts are downloadable
barcodes	code 39, extended code 39, code 93, code 128 (subset A, B, C) codabar, interleave 2 of 5 EAN-8, EAN-13, EAN-128 UPC-E, UPC-A, E2&5
2D barcodes	pdf - 417, RSS
graphic	bmp format
memory	8MB SDRAM, 4M flash
interfaces	RS-232C, centronics, ethernet, USB
media	label and receipt
media width	1.57" - 4.41" / 40mm - 112mm
media roll	3" / 80mm (IN), MAX 7.85" / 200mm (OUT)
ribbon	wax, resin and hybrid
ribbon width	1.38" - 4.52" / 35mm - 115mm
ribbon roll	1" / 25.4mm (IN), MAX 2.52" / 64mm (OUT)
physical size	265 (w) x 425 (d) x 335 (h) mm 10.43 (w) x 16.73 (d) x 13.19 (h) inches
weight	14 Kg / 30.8 lbs
electrical	100 / 117V AC or 220 / 240V AC with 50 / 60Hz by factory default
environment	5 ~ 40°C & 15 ~ 85% RH non - condensing
accessories	Windows 98 / 2000 / XP driver label design software (Dr. Label Lite) operational manual, AC cable
optional features	stainless steel cover, auto cutter (factory option), internal rewinder (factory option), external rewinder, PCMCIA bridge (factory option), dr. label standard edition (label printing software), dr. label professional edition (ODBC function, 2D barcode)

**Specifications are subject to change without notice*

Thank you to our loyal customers for their continued support