OVERHEAD TRACK SCALES

/ISO 900





Designed for weighing loads which move on tracks of scales. Scale can cooperate with device for evaluating meat content. LCD backlit indicator installed on a wire.


Overhead scales are manufactured either in galvanized and in stainless steel version, as dual range weighing instruments. They are equipped with stainless steel backlit LCD measuring indicator PUE C/31H.

Special software allows for cooperation with a device for meat content evaluation.





Summing function

2 years warranty period



CE





CAUTION!

- weighing track in place of installation of the scale must be positioned horizontally with maximal tolerance +/- 10 mm
- z dimension can be omitted of: Z < 80 % D

Technical data:

	WPT/2K 300/600	WPT/2K 300/600H
Max capacity	300/600 kg	300/600 kg
Readability	0,1/0,2 kg	0,1/0,2 kg
Tare range	-600 kg	-600 kg
Scale construction	galvanized	stainless steel
Track length	max. 800 mm	
Working temperature	-10° - +40 °C	
Output signal	RS 232	
Power supply	230V, 50Hz	
Display	LCD (backlit)	

Additional equipment:

RACK FOR HEAD
LCD DISPLAY
LARGE SIZE LCD DISPLAY
"KAFKA" THERMAL PRINTER
NEEDLE PRINTER "EPSON"
COMPUTER SOFTWARE: PW-WIN 2005
COMPUTER SOFTWARE: RAD-KEY 2000
RS 232/RS 485 CONVERTER
EXTERNAL POWER OUTPUT

Zakład Mechaniki Precyzyjnej RADWAG

26-600 Radom, Bracka Street 28 POLAND Phone: +48 48 3848800 Fax: +48 48 3850010 Sales department: +48 48 3668006 www.radwag.com e-mail:export@radwag.com

DISTRIBUTOR: